

REFERENCES

- [1] Cheng X, Wang Z, Nakamoto K, Yamazaki K. (2011) A study on the micro tooling for micro/nano milling. *International Journal of Advanced Manufacturing Technology*, 53:523-533.
- [2] Wang JS, Gong YD, Abba G, Chen K, Shi JS, Cai GQ. (2008) Surface generation analysis in micro end-milling considering the influences of grain. *Microsystem Technologies*, 14(7):937-942.
- [3] Li KM, Wang SL. (2014) Effect of tool wear in ultrasonic vibration-assisted micro-milling. *Proceedings of the Institution of Mechanical Engineers Part B Journal of Engineering Manufacture*, 228(6):874-855.
- [4] Ucin I, Aslantas K, Bedir F. (2013) An experimental investigation of the effect of coating material on tool wear in micro milling of Inconel 718 super alloy. *Wear*, 300(1):8-19.
- [5] Fink J, Thery M, Azioune A, Dupont R, Chatelain F, Bornens M, Piel M. (2007) Comparative study and improvement of current cell micro-patterning techniques. *Lab on a Chip*, 7(6):672-680.
- [6] Kancharla VV, Chen S. (2002) Fabrication of biodegradable polymeric micro-devices using laser micromachining. *Biomedical Microdevices*, 4(2):105-109.
- [7] Shahrom MS, Yahya NM, Yusoff AR. (2013) Taguchi method approach on effect of lubrication condition on surface roughness in milling operation. *Procedia Engineering*, 53:594-599.
- [8] Kajaria S, Chittipolu S, Adera S, Hung WNP. (2012) Micromilling in minimum quantity lubrication. *Machining Science and Technology*, 16(4):524-546.
- [9] Yerkes KL, Dorian J. (1999) Micro-cooler for chip-level temperature control. *SAE Technical Paper*, 01-1404.
- [10] Burton G, Goo CS, Zhang Y, Jun MB. (2014) Use of vegetable oil in water emulsion achieved through ultrasonic atomization as cutting fluids in micro-milling. *Journal of Manufacturing Processes*, 16:405-413.
- [11] Zhong W, Zhao D, Wang X. (2010) A comparative study on dry milling and little quantity lubricant milling based on vibration signals. *International Journal of Machine Tools and Manufacture*, 50(12):1057-1064.
- [12] Machado AR, Wallbank J. (1997) The effect of extremely low lubricant volumes in machining. *Wear*, 210(1):76-82.
- [13] Superkar SD, Clarens AF, Stephenson DA, Skerlos SJ. (2012) Performance of supercritical carbon dioxide sprays as coolants and lubricants in representative metalworking operations. *Journal of Materials Processing Technology*, 212(12):2652-2658.
- [14] Machai C, Iqbal A, Biermann D, Upmeier T, Schumann S. (2013) On the effects of cutting speed and cooling methodologies in grooving operation of various tempers of β -titanium alloy. *Journal of Materials Processing Technology*, 213(7):1027-1037.
- [15] Shaikh V, Bouberi N, Scharf TW. (2014) Analyzing the effectiveness of microlubrication using a vegetable oil-based metal working fluid during end milling AISI 1018 steel. *International Journal of Manufacturing Engineering*, 2014: 1-13.
- [16] Biermann D, Iovkov I. (2013) Modelling and simulation of heat input in deep-hole drilling with drills and MQL. *Procedia CIRP*, 8:87-92.
- [17] Rakurty CS, Vrela PI, Balaji AK. (2013) Effects of targeted minimum quantity fluid (MQF) application on surface integrity. *Procedia CIRP*, 8:461-467.
- [18] Chae J, Park SS, Freiheit T. (2006) Investigation of micro-cutting operations. *International Journal of Machine Tools and Manufacture*, 46(3-4):313-332.
- [19] Okonkwo UC, Okokpuije IP, Sinebe JE, Ezugwu AK. (2015) Comparative analysis of aluminium surface roughness in end-milling under dry and minimum quantity lubrication (MQL) conditions. *Manufacturing Review*, 30(2): 1-11.